NSN 5305-00-225-6866

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-225-6866

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.422 inches and 0.516 inches
Fastener Length:
Between 0.484 inches and 0.516 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.218 inches and 0.226 inches
Head Height:
Between 0.134 inches and 0.138 inches
Spline Minor Diameter:
Between 0.116 inches and 0.118 inches
Spline Major Diameter:
Between 0.135 inches and 0.137 inches
Spline Width:
Between 0.028 inches and 0.030 inches
Internal Drive Style:
Six spline
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Material Specification:
66 federal standard all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unc

NSN 5305-00-225-6866

Socket Head Cap Screw - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0