## NSN 5305-00-225-6893

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-225-6893 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.125 inches **Fastener Length:** 0.874 inches **Head Style:** Knurled no. 4 **Head Diameter:** 0.437 inches **Head Height:** 0.251 inches **First Diameter From Head:** 0.190 inches **Second Diameter From Head:** 0.123 inches **Third Diameter From Head:** 0.190 inches **Fourth Diameter From Head:** 0.128 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.187 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.375 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.687 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 0.749 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 4 Material: Copper alloy

Cadmium

**Surface Treatment:** 

## NSN 5305-00-225-6893

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0