

View Online at <https://aerobasegroup.com/nsn/5305-00-225-6943>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.247 inches

Fastener Length:

0.500 inches

Head Style:

Flat countersunk

Head Diameter:

0.507 inches

Locking Feature:

Patch threads or strip threads

Internal Drive Style:

Cross recess type 1

End Application:

W/s: helicopter, mh-53e; helicopter, search and rescue, hh-60h; helicopter, carrier based asw, sh-60f; fire pumps; helicopter, uscg search and rescue, hh-60j; aircraft, c-2a (reprocured); loader, scoop type; ded 4/4 w/4 1-1/2 or 5 cy gp bucket (cce); helicopter advance attack, ah-1w; forrestal class cv

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

20

Countersink Angle:

82.0 degrees

Material:

Steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020

Surface Treatment:

Cadmium and chromate

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0