

View Online at <https://aerobasegroup.com/nsn/5305-00-226-4831>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.875 inches and 1.062 inches

Fastener Length:

Between 1.438 inches and 1.500 inches

Head Style:

Hexagon

Head Height:

Between 0.195 inches and 0.211 inches

Width Between Flats:

Between 0.489 inches and 0.500 inches

End Application:

Mrap buffalo mk2a2; mrap - cougar cat1 a2; medium mine protected vehicle - mmpv

Thread Diameter:

0.312 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 38.0 rockwell c

Surface Finish:

63.0 microinches threads

Material:

Steel

Material Specification:

Sae j429 grade 8 assn standard single material response or astm a354 grade bd assn standard single material response

Surface Treatment:

Zinc and chromate

Surface Treatment Specification:

Astm b633 type 2 sc 3 assn standard single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

2 type and 10p style and 8 grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0