## NSN 5305-00-226-7605

**Thread Class:** 

Right-hand

**Thread Direction:** 

За

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-226-7605

Thread Length:
Between 1.210 inches and 1.500 inches
Fastener Length:
Between 1.710 inches and 1.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.365 inches and 0.375 inches
Head Height:
Between 0.244 inches and 0.250 inches
Hole Diameter:
0.047 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
Between 0.1875 inches and 0.1900 inches
Hole Quantity:
3
Hole Type:
Hole Type: Drilled
**
Drilled
Drilled Thready Qty Per Inch (tpi):
Drilled Thready Qty Per Inch (tpi): 28
Drilled  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi):
Drilled  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 170000 pounds per square inch
Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating:
Drilled  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 170000 pounds per square inch  Hardness Rating: 38.0 rockwell c and 45.0 rockwell c
Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength:
Drilled  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 170000 pounds per square inch  Hardness Rating: 38.0 rockwell c and 45.0 rockwell c  Minimum Yield Strength: 150000 pounds per square inch
Thready Qty Per Inch (tpi):  28  Min. Tensile Strength (psi):  170000 pounds per square inch  Hardness Rating:  38.0 rockwell c and 45.0 rockwell c  Minimum Yield Strength:  150000 pounds per square inch  Hole Configuration Style:
Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Hole Configuration Style: Round internal hexagon
Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Hole Configuration Style: Round internal hexagon Material:
Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 170000 pounds per square inch  Hardness Rating: 38.0 rockwell c and 45.0 rockwell c  Minimum Yield Strength: 150000 pounds per square inch  Hole Configuration Style: Round internal hexagon  Material: Steel
Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Steel Surface Treatment:
Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Steel Surface Treatment: Cadmium and chromate
Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification:

## NSN 5305-00-226-7605

Socket Head Cap Screw - Page 2 of 2



Inread Series Designator:
Unf
Specification Or Standard:
6 type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0