NSN 5305-00-227-1431

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-227-1431 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.407 inches and 0.500 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Round **Head Diameter:** Between 0.299 inches and 0.309 inches **Head Height:** Between 0.110 inches and 0.120 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Primary Washer Outside Diameter:** 0.392 inches **Primary Washer Style:** Flat **Primary Washer Material Thickness:** 0.109 inches Material: Steel comp 1020 primary washer or rubber synthetic primary washer **Material Specification:** Mil-s-7952 military specification 1st material response primary washer or ams 3208 assn standard 2nd material response primary washer **Surface Treatment:** Paint top of head **Surface Treatment Specification:** Qq-p-416, type 2, cl2 federal specification all treatment responses **Thread Series Designator:**

Unc

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-227-1431

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7952 spec.