## NSN 5305-00-227-1465

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-227-1465



Threa	d Class:
3a	
Threa	d Direction:
Right-	hand
Threa	Id Length:
Betwe	en 1.047 inches and 1.156 inches
Faste	ner Length:
Betwe	een 1.109 inches and 1.156 inches
Head	Style:
Flat cl	hamfer
Head	Diameter:
Betwe	een 0.262 inches and 0.270 inches
Head	Height:
Betwe	een 0.159 inches and 0.164 inches
Hole	Diameter:
0.047	inches
Intern	al Drive Style:
Hexa	gon
Threa	d Diameter:
0.164	inches
Width	Across Flats:
Betwe	en 0.141 inches and 0.143 inches
Hole	Quantity:
6	
Hole	Туре:
Drilleo	1
Threa	idy Qty Per Inch (tpi):
32	
Min. 1	Fensile Strength (psi):
80000	) pounds per square inch
Hardr	ness Rating:
80.0 r	ockwell b
Minim	num Yield Strength:
30000	) pounds per square inch
Hole	Configuration Style:
Round	d internal hexagon
Mater	ial:
Steel	comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel
Mater	ial Specification:
66 fec	leral standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 66

federal standard 4th material response or 66 federal standard 5th material response or astm-a493 aisi xm-7 assn standard 6th material response

## Surface Treatment:

Passivate

## NSN 5305-00-227-1465

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0