NSN 5305-00-227-1488

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-227-1488 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** Between 0.730 inches and 0.770 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.262 inches and 0.270 inches **Head Height:** Between 0.159 inches and 0.164 inches **First Diameter From Head:** Between 0.118 inches and 0.128 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.480 inches and 0.520 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Color red epoxy no. 1985632-1 Material: Stainless steel **Surface Treatment:** Passivate and paint **Surface Treatment Specification:** Mil-f-14072 e-300 military specification 1st treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-227-1488

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.