

View Online at <https://aerobasegroup.com/nsn/5305-00-227-7353>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.208 inches and 0.228 inches

Fastener Length:

Between 0.740 inches and 0.760 inches

Head Style:

Pan

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.122 inches and 0.133 inches

First Diameter From Head:

Between 0.120 inches and 0.140 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.522 inches and 0.542 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

1

Special Features:

Ms51958-65 screw has been modified in accordance with national security agency drawing no. 0n080025-2

Material:

Stainless steel

Material Specification:

Qq-s-763, 300 series federal specification single material response or federal standard 66, 300 series federal standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Test Data Document:

96906-ms51958 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0