

View Online at <https://aerobasegroup.com/nsn/5305-00-227-7353>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.208 inches and 0.228 inches

**Fastener Length:**

Between 0.740 inches and 0.760 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.357 inches and 0.373 inches

**Head Height:**

Between 0.122 inches and 0.133 inches

**First Diameter From Head:**

Between 0.120 inches and 0.140 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.522 inches and 0.542 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Ms51958-65 screw has been modified in accordance with national security agency drawing no. 0n080025-2

**Material:**

Stainless steel

**Material Specification:**

Qq-s-763, 300 series federal specification single material response or federal standard 66, 300 series federal standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Test Data Document:**

96906-ms51958 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0