NSN 5305-00-228-4002

Setscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-228-4002

Thread Class:
3a
Thread Direction:
Right-hand Thread Length:
Thread Length: Between 0.493 inches and 0.569 inches
Fastener Length: Between 0.564 inches and 0.569 inches
Head Style: Flat chamfer
Head Diameter:
Between 0.365 inches and 0.375 inches
Head Height:
Between 0.244 inches and 0.250 inches
Hole Diameter:
0.047 inches
Point Style:
Flat
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
Between 0.188 inches and 0.190 inches
Hole Quantity:
2
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Hole Configuration Style:
Round
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Material Specification:

66 federal standard all material responses

NSN 5305-00-228-4002

Setscrew - Page 2 of 2

A003b0



Surface Treatment:
Passivate
Surface Treatment Specification:
171, finish 5.4.1 military standard single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: