## NSN 5305-00-229-3614

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-229-3614 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.265 inches and 0.295 inches **Fastener Length:** Between 0.802 inches and 0.822 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.118 inches and 0.130 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.507 inches and 0.557 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 e 300 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5305-00-229-3614

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.