Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-229-3615

| Threa | d Class: |
|----------|--|
| 2a | |
| Threa | d Direction: |
| Right- | hand |
| Threa | d Length: |
| Betwe | en 0.265 inches and 0.295 inches |
| Faste | ner Length: |
| Betwe | en 1.115 inches and 1.135 inches |
| Head | Style: |
| Filliste | r |
| Head | Diameter: |
| Betwe | en 0.292 inches and 0.313 inches |
| Head | Height: |
| Betwe | en 0.118 inches and 0.130 inches |
| First [| Diameter From Head: |
| Betwe | en 0.125 inches and 0.135 inches |
| Distar | nce From Largest Bearing Surface Of Head To End Of First Diameter: |
| Betwe | en 0.820 inches and 0.870 inches |
| Intern | al Drive Style: |
| Slot | |
| Threa | d Diameter: |
| 0.190 | inches |
| Threa | dy Qty Per Inch (tpi): |
| 32 | |
| Extern | nally Relieved Body Diameter Quantity: |
| 1 | |
| Mater | ial: |
| Steel of | comp 303 |
| Mater | al Specification: |
| Astm a | a582 assn standard single material response |
| Surfac | ce Treatment: |
| Passiv | vate |
| Surfac | ce Treatment Specification: |
| Mil-f-1 | 4072 e 300 military specification single treatment response |
| Threa | d Series Designator: |
| Unf | |
| Shelf | Life: |
| N/a | |
| Unit C | of Measure: |
| | |
| Demil | itarization: |
| No | |

Externally Relieved Body Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-f-14072 spec.