NSN 5305-00-229-8633

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-229-8633 **Thread Direction:** Right-hand Thread Length: 0.154 inches Fastener Length: 0.246 inches **Head Style:** Pan no. 2 **Head Diameter:** 0.280 inches **Head Height:** Between 0.032 inches and 0.038 inches First Diameter From Head: 0.123 inches **Second Diameter From Head:** 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.069 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.092 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.093 inches **Features Provided:** Casehardened **Nonstandard Thread Pitch Diameter:** +0.0733/+0.0753 inches Thready Qty Per Inch (tpi): 64 **Askewed Head Angle:** 90.0 degrees **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 630 **Material Specification:** Ams 5643 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-std-171 military standard single treatment response

NSN 5305-00-229-8633

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-std-171 spec.