NSN 5305-00-230-2056

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-230-2056

view Offilitie at https://aerobasegroup.com/nsn/3303-00-230-2000
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.192 inches and 0.250 inches
Fastener Length:
Between 0.220 inches and 0.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.112 inches and 0.118 inches
Head Height:
Between 0.070 inches and 0.073 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.073 inches
Width Across Flats:
Between 0.063 inches and 0.064 inches
Thready Qty Per Inch (tpi):
72
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Material:
Steel
Material Specification:
66 federal standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
NI/a

N/a

NSN 5305-00-230-2056

Socket Head Cap Screw - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0