## NSN 5305-00-230-2121

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-230-2121 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.302 inches and 0.328 inches **Fastener Length:** Between 1.359 inches and 1.391 inches **Head Style:** Hexagon **Head Height:** Between 0.096 inches and 0.110 inches Width Between Flats: Between 0.244 inches and 0.250 inches **First Diameter From Head:** Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.031 inches and 1.089 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Nylon strip element in threads Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 171, finish no. 5.4.1 military standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-230-2121

Externally Relieved Body Screw - Page 2 of 2



| _  |    | •• | • • |     |     |   |    |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш  | 112 | rız | 211 | n | ٠. |
|    |    |    |     |     |     |   |    |

No

Fiig:

A003b0