

View Online at <https://aerobasegroup.com/nsn/5305-00-230-5113>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.160 inches and 0.180 inches

**Fastener Length:**

Between 0.360 inches and 0.370 inches

**Head Style:**

Headless (setscrew)

**Point Length:**

Between 0.180 inches and 0.210 inches

**Point Style:**

Flat

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.164 inches

**Width Across Flats:**

Between 0.078 inches and 0.080 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

248.0 brinell standard and 341.0 brinell standard

**Point Chamfer Angle:**

Between 29.0 degrees and 31.0 degrees

**Special Features:**

2 holes 0.031 in. Min, 0.035 in. Maximum diameter drilled horizontally through 2 walls 85 to 95 degrees apart, 0.045 in. Min, 0.055 in. Maximum distance from top of screw

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard single material response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0