## NSN 5305-00-231-8827

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-231-8827 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.151 inches and 0.161 inches **Fastener Length:** Between 0.428 inches and 0.448 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.168 inches and 0.178 inches **Head Height:** Between 0.059 inches and 0.069 inches **First Diameter From Head:** Between 0.107 inches and 0.112 inches **Second Diameter From Head:** Between 0.075 inches and 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.025 inches and 0.030 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.267 inches and 0.297 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 **Product Name:** Navy special project Material: Steel comp 303se or steel comp 303 **Surface Treatment:** Passivate **Thread Series Designator:** Unc Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-00-231-8827

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0