## NSN 5305-00-232-0488

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-232-0488 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.563 inches **Fastener Length:** Between 3.593 inches and 3.596 inches **Head Style:** Flat chamfer **Head Diameter:** 0.937 inches **Head Height:** 0.250 inches **First Diameter From Head:** Between 0.500 inches and 0.505 inches **Second Diameter From Head:** Between 0.681 inches and 0.686 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 2.000 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 2.843 inches and 2.846 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.562 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 **Special Features:** Thread relief 0.460 in. Min 0.465 in. Maximum dia, 0.187 in. Wide Material: Steel comp 303 **Material Specification:** 66 federal standard single material response **Thread Series Designator:** Unf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-00-232-0488

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0