NSN 5305-00-232-2849



Thumbscrew - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-232-2849 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.309 inches and 0.380 inches **Fastener Length:** 2.380 inches **Head Style:** Knurled no. 1 **Head Diameter:** 1.380 inches **Head Height:** 0.560 inches **Shoulder Diameter:** 0.342 inches first shoulder and 0.343 inches first shoulder **Shoulder Length:** 2.000 inches first shoulder **Point Style:** Flat **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c **Shoulder Shape:** Round first shoulder **Special Features:** Bearing surface of head undercut 0.156 in. Deep by 0.870 in. Dia. Material: Steel comp 4130 **Material Specification:** Mil-s-5000 cond e military specification single material response **Surface Treatment:** Cadmium Qq-p-416 type 2 cl 2 federal specification single treatment response

Surface Treatment Specification: Thread Series Designator: Unf Shelf Life: N/a

NSN 5305-00-232-2849

Thumbscrew - Page 2 of 2



ı	In	iŧ	Ωf	M	22	em	re:
L	JII	ıι	vı	IVI	ca.	วน	ıe.

--

Demilitarization:

Yes - demil/mli

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.