## NSN 5305-00-233-8641

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-233-8641 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.593 inches and 0.657 inches **Fastener Length:** Between 1.609 inches and 1.641 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.368 inches and 0.378 inches **Head Height:** Between 0.128 inches and 0.138 inches **First Diameter From Head:** Between 0.129 inches and 0.161 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.984 inches and 1.016 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Stainless steel **Material Specification:** Qq-s-763, 300 series federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** 171, finish no. 5.4.1 military standard single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-233-8641

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0