NSN 5305-00-233-8642

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-233-8642 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.374 inches and 0.438 inches **Fastener Length:** Between 1.890 inches and 1.922 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.368 inches and 0.378 inches **Head Height:** Between 0.128 inches and 0.138 inches **First Diameter From Head:** Between 0.131 inches and 0.134 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.484 inches and 1.516 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Stainless steel or steel **Material Specification:** Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or 18-8 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** 171, finish no. 5.4.1 military standard single treatment response **Thread Series Designator:** Unf

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-00-233-8642

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0