## NSN 5305-00-234-6199

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-234-6199 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.219 inches **Fastener Length:** 0.562 inches **Head Style:** Hexagon **Head Height:** Between 0.111 inches and 0.125 inches Width Between Flats: Between 0.244 inches and 0.250 inches **Locking Feature:** Strip threads First Diameter From Head: Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.343 inches **Internal Drive Style:** Slot Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Head fine grit sand blast non-reflective matte Material: Steel comp 302 or steel comp 303 **Material Specification:** Qq-3-763, cond a federal specification 1st material response or astm a582, cond ad a assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Astm a380 assn standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-234-6199

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0