
Socket Head Cap Screw - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.559 inches and 0.641 inches Fastener Length: Between 0.609 inches and 0.641 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches Locking Feature: Strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.094 inches and 0.095 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 155000 pounds per square inch Material: Steel fastener Surface Treatment: Cadmium fastener and chromate fastener Surface Treatment Specification: Qq-p-416, type 2 class 2 federal specification single treatment response fastener **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard Shelf Life: N/a

NSN 5305-00-234-7229

Socket Head Cap Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0