NSN 5305-00-234-7773



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-234-7773 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.656 inches and 0.770 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.685 inches and 0.762 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Mrap rg-33 **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Stainless steel or steel **Screw Material Specification:** Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or 18-8 assn standard 2nd material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 3 type and 2c style

Shelf Life: N/a **Unit Of Measure:** Demilitarization: No

NSN 5305-00-234-7773

Machine Screw - Page 2 of 2



Fiig:

A500d0