

View Online at <https://aerobasegroup.com/nsn/5305-00-234-7773>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.656 inches and 0.770 inches

**Fastener Length:**

Between 0.969 inches and 1.000 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.685 inches and 0.762 inches

**Internal Drive Style:**

Cross recess type 1

**End Application:**

Mrap rg-33

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Screw Material:**

Stainless steel or steel

**Screw Material Specification:**

Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or 18-8 assn standard 2nd material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Specification Or Standard:**

3 type and 2c style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0