

View Online at <https://aerobasegroup.com/nsn/5305-00-234-7813>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.675 inches and 0.818 inches

Fastener Length:

Between 0.984 inches and 1.016 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.600 inches and 0.656 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.312 inches

Width Across Flats:

Between 0.188 inches and 0.190 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Countersink Angle:

Between 80.0 degrees and 84.0 degrees

Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

4 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0