NSN 5305-00-234-7813

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-234-7813 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.675 inches and 0.818 inches **Fastener Length:** Between 0.984 inches and 1.016 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.600 inches and 0.656 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 84.0 degrees Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 4 type Shelf Life:

N/a

NSN 5305-00-234-7813

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0