## NSN 5305-00-234-8781

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-234-8781

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.199 inches
Fastener Length:
0.199 inches
Head Style:
Flat countersunk undercut
Head Diameter:
Between 0.156 inches and 0.172 inches
Head Height:
0.051 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.086 inches
Thready Qty Per Inch (tpi):
56
Countersink Angle:
82.0 degrees
Screw Material:
Stainless steel
Stainless steel  Screw Material Specification:
Screw Material Specification:
Screw Material Specification:  Qq-s-763 federal specification single material response
Screw Material Specification:  Qq-s-763 federal specification single material response  Screw Surface Treatment:
Screw Material Specification:  Qq-s-763 federal specification single material response  Screw Surface Treatment:  Passivate
Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification:
Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc
Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life:
Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a
Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:
Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:
Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: