NSN 5305-00-234-8785

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-234-8785 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.106 inches and 0.113 inches **Hole Diameter:** 0.046 inches First Diameter From Head: Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): 32 **Hole Configuration Style: Externally Relieved Body Diameter Quantity:** Material: Stainless steel **Material Specification:** Qq-s-634 federal specification single material response or qq-s-637 federal specification single material response **Surface Treatment:** Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

NSN 5305-00-234-8785

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0