NSN 5305-00-235-5758

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-235-5758 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.230 inches and 0.250 inches **Fastener Length:** Between 0.687 inches and 0.730 inches **Head Style:** Pan no. 2 **Head Diameter:** 0.230 inches **Head Height:** 0.075 inches **First Diameter From Head:** 0.128 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.437 inches and 0.500 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 4140 **Material Specification:** Mil-s-5626 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 3 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-235-5758

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.