## NSN 5305-00-235-5777

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-235-5777



### Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 1.001 inches and 1.125 inches Fastener Length: Between 1.063 inches and 1.125 inches Head Style: Flat chamfer Head Diameter: Between 0.306 inches and 0.313 inches Head Height:

Between 0.103 inches and 0.118 inches

#### Hole Diameter:

#### 0.038 inches

Internal Drive Style:

Torque set

#### **Thread Diameter:**

0.190 inches

#### Hole Quantity:

2

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

#### **Screw Material:**

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

#### **Screw Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military

specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

#### Screw Surface Treatment:

Cadmium and chromate

#### Screw Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

#### Head Hole Configuration Style:

Round

#### **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

# NSN 5305-00-235-5777

Machine Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.

