

View Online at <https://aerobasegroup.com/nsn/5305-00-235-6181>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.106 inches and 0.188 inches

**Fastener Length:**

Between 0.156 inches and 0.188 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.200 inches and 0.225 inches

**Head Height:**

Between 0.055 inches and 0.067 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

55000 pounds per square inch

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Screw Material:**

Copper alloy

**Screw Material Specification:**

Qq-b-613 federal specification single material response or qq-b-626 federal specification single material response or qq-w-321 federal specification single material response

**Screw Surface Treatment Specification:**

Vsf-30002-59 fscm 13923 mfr ref single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

1 type and 2s style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0