NSN 5305-00-235-7286

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-235-7286 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.320 inches and 0.380 inches **Fastener Length:** Between 1.020 inches and 1.040 inches **Head Style:** Hexagon **Head Height:** Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches **First Diameter From Head:** Between 0.195 inches and 0.205 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.660 inches and 0.700 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, type 2 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

NSN 5305-00-235-7286

Externally Relieved Body Screw - Page 2 of 2



Unit	Of	Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.