NSN 5305-00-236-1375

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-236-1375 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.095 inches and 0.188 inches **Fastener Length:** Between 0.157 inches and 0.188 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.221 inches and 0.226 inches **Head Height:** Between 0.074 inches and 0.086 inches **Hole Diameter:** 0.038 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.138 inches **Hole Quantity:** 2 Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 140000 pounds per square inch Hardness Rating: Between 248.0 brinell standard and 341.0 brinell standard **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5735 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Head Hole Configuration Style: Thread Series Designator:**

Round Unjc Shelf Life: N/a

NSN 5305-00-236-1375

Machine Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A500d0