

View Online at <https://aerobasegroup.com/nsn/5305-00-236-3782>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.202 inches and 0.220 inches

Fastener Length:

Between 0.510 inches and 0.530 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.363 inches and 0.375 inches

Head Height:

Between 0.244 inches and 0.250 inches

Shoulder Diameter:

0.158 inches first shoulder and 0.160 inches first shoulder

Shoulder Length:

0.258 inches first shoulder and 0.260 inches first shoulder

Internal Drive Style:

Hexagon

Thread Diameter:

0.112 inches

Width Across Flats:

Between 0.188 inches and 0.190 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

80000 pounds per square inch

Minimum Yield Strength:

30000 pounds per square inch

Shoulder Shape:

Round first shoulder

Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0