## NSN 5305-00-236-3782

Shoulder Screw - Page 1 of 2

3a

40

View Online at https://aerobasegroup.com/nsn/5305-00-236-3782



## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.202 inches and 0.220 inches Fastener Length: Between 0.510 inches and 0.530 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.363 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Shoulder Diameter:** 0.158 inches first shoulder and 0.160 inches first shoulder Shoulder Length: 0.258 inches first shoulder and 0.260 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Minimum Yield Strength:** 30000 pounds per square inch Shoulder Shape: Round first shoulder Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

## NSN 5305-00-236-3782

Shoulder Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

