## NSN 5305-00-237-6488

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-237-6488 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.249 inches and 1.380 inches **Fastener Length:** Between 1.320 inches and 1.380 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 8630 or steel comp 4037 **Screw Material Specification:** Mil-s-6050sjgcams 6300 military specification 1st material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unjf **Specification Data:** 80205-nas604 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-00-237-6488

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050sjgcams spec.