Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-238-7000

Thread	Class:
IIIIcau	GIA35 .

3a

Thread Direction:

Right-hand

Thread Length:

1.500 inches

Fastener Length:

1.750 inches

Head Style:

Flat chamfer

Head Diameter:

0.750 inches

Head Height:

0.500 inches

Internal Drive Style:

.....

Hexagon

Thread Diameter:

0.500 inches

Width Across Flats:

0.375 inches

Thready Qty Per Inch (tpi):

13

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 43.0 rockwell c

Minimum Yield Strength:

130000 pounds per square inch

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

NSN 5305-00-238-7000

Socket Head Cap Screw - Page 2 of 2

Mil-std (military Standard):

Mil-s-5626 spec.

