## NSN 5305-00-238-7007

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-238-7007 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.122 inches and 0.212 inches **Fastener Length:** 0.312 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **First Diameter From Head:** Between 0.146 inches and 0.150 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.090 inches and 0.100 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Entire thd grooved longitudinally, 0.062 in. W by 0.060 in. Deep Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 **Material Specification:** Aisi assn standard all material responses or sae assn standard all material responses or federal standard 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-00-238-7007

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0