NSN 5305-00-238-7013

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-238-7013 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.345 inches and 0.376 inches **Fastener Length:** Between 0.907 inches and 0.938 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** Between 0.115 inches and 0.120 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.562 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project Material: Steel comp 303se or steel comp 304l or steel comp 302b or steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-00-238-7013

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0