NSN 5305-00-238-7372

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-238-7372 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.371 inches and 0.438 inches **Fastener Length:** Between 1.443 inches and 1.490 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.497 inches and 0.507 inches **Shoulder Diameter:** 0.280 inches and 0.281 inches first shoulder **Shoulder Length:** 1.052 inches and 1.072 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Product Name:** Navy special project Material: Steel comp h11 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ps-13145, fscm 18355 mfr ref single treatment response **Thread Series Designator:**

Unjf Shelf Life:

N/a

NSN 5305-00-238-7372

Shoulder Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0