Hexagon Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-240-0096

3aThread Direction:Right-handThread Length:0.750 inchesFastener Length:1.250 inchesHead Style:HexagonHead Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesThread Diameter:0.500 inchesFeatures Provided:Finished headThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):80000 pounds per square inchMinimum Yield Strength:40000 pounds per square inchSpecial Features:
Right-handThread Length:0.750 inchesFastener Length:1.250 inchesHead Style:Head Style:HexagonHead Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesThread Diameter:0.500 inchesFeatures Provided:Finished headThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):80000 pounds per square inchMinimum Yield Strength:40000 pounds per square inch
Thread Length:0.750 inchesFastener Length:1.250 inchesHead Style:Head Style:HexagonHead Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesThread Diameter:0.500 inchesFeatures Provided:Finished headThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):80000 pounds per square inchMinimum Yield Strength:40000 pounds per square inch
0.750 inches Fastener Length: 1.250 inches Head Style: Head Style: Hexagon Head Height: Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.736 inches and 0.750 inches Thread Diameter: 0.500 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 80000 pounds per square inch Minimum Yield Strength: 40000 pounds per square inch
Fastener Length:1.250 inchesHead Style:HexagonHead Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesThread Diameter:0.500 inchesFeatures Provided:Finished headThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):80000 pounds per square inchMinimum Yield Strength:40000 pounds per square inch
<ul> <li>1.250 inches</li> <li>Head Style:</li> <li>Hexagon</li> <li>Head Height:</li> <li>Between 0.302 inches and 0.323 inches</li> <li>Width Between Flats:</li> <li>Between 0.736 inches and 0.750 inches</li> <li>Thread Diameter:</li> <li>0.500 inches</li> <li>Features Provided:</li> <li>Finished head</li> <li>Thready Qty Per Inch (tpi):</li> <li>13</li> <li>Min. Tensile Strength (psi):</li> <li>80000 pounds per square inch</li> <li>Minimum Yield Strength:</li> <li>40000 pounds per square inch</li> </ul>
Head Style:HexagonHead Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesThread Diameter:0.500 inchesFeatures Provided:Finished headThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):80000 pounds per square inchMinimum Yield Strength:40000 pounds per square inch
Hexagon Head Height: Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.736 inches and 0.750 inches Thread Diameter: 0.500 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 80000 pounds per square inch Minimum Yield Strength: 40000 pounds per square inch
Head Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesThread Diameter:0.500 inchesFeatures Provided:Finished headThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):80000 pounds per square inchMinimum Yield Strength:40000 pounds per square inch
Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.736 inches and 0.750 inches Thread Diameter: 0.500 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 80000 pounds per square inch Minimum Yield Strength: 40000 pounds per square inch
<ul> <li>Width Between Flats:</li> <li>Between 0.736 inches and 0.750 inches</li> <li>Thread Diameter:</li> <li>0.500 inches</li> <li>Features Provided:</li> <li>Finished head</li> <li>Thready Qty Per Inch (tpi):</li> <li>13</li> <li>Min. Tensile Strength (psi):</li> <li>80000 pounds per square inch</li> <li>Minimum Yield Strength:</li> <li>40000 pounds per square inch</li> </ul>
Between 0.736 inches and 0.750 inches Thread Diameter: 0.500 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 80000 pounds per square inch Minimum Yield Strength: 40000 pounds per square inch
Thread Diameter: 0.500 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 80000 pounds per square inch Minimum Yield Strength: 40000 pounds per square inch
0.500 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 80000 pounds per square inch Minimum Yield Strength: 40000 pounds per square inch
Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 80000 pounds per square inch Minimum Yield Strength: 40000 pounds per square inch
Finished head Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 80000 pounds per square inch Minimum Yield Strength: 40000 pounds per square inch
Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 80000 pounds per square inch Minimum Yield Strength: 40000 pounds per square inch
<ul> <li>13</li> <li>Min. Tensile Strength (psi):</li> <li>80000 pounds per square inch</li> <li>Minimum Yield Strength:</li> <li>40000 pounds per square inch</li> </ul>
Min. Tensile Strength (psi):80000 pounds per square inchMinimum Yield Strength:40000 pounds per square inch
80000 pounds per square inch Minimum Yield Strength: 40000 pounds per square inch
Minimum Yield Strength: 40000 pounds per square inch
40000 pounds per square inch
Special Features:
Self locking feature per mil-f-18240
Material:
Nickel alloy 400
Material Specification:
Qq-n-281, class a federal specification single material response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0