NSN 5305-00-241-5483

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-241-5483 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.258 inches and 0.390 inches **Fastener Length:** Between 0.470 inches and 0.530 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **First Diameter From Head:** Between 0.144 inches and 0.149 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.140 inches and 0.150 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Stainless steel **Material Specification:** Qq-s-763 federal specification single material response or federal standard 66 300 series federal standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-241-5483

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0