## NSN 5305-00-241-8273

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-241-8273 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.320 inches and 0.360 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.094 inches and 0.097 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.609 inches and 0.680 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel **Material Specification:** Qq-s-763 federal specification single material response or federal standard 66 300 series federal standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-00-241-8273

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0