NSN 5305-00-242-9140

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-242-9140 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.220 inches and 0.240 inches **Fastener Length:** Between 0.520 inches and 0.530 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.092 inches and 0.097 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.290 inches and 0.300 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment:** Oxide film **Surface Treatment Specification:** Mil-q-13924, cl 4 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-242-9140

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-q-13924 spec.