NSN 5305-00-243-4877

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-243-4877 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.120 inches and 0.130 inches **Fastener Length:** 0.625 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.307 inches and 0.312 inches **Head Height:** Between 0.297 inches and 0.328 inches **First Diameter From Head:** Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.412 inches and 0.432 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Point non-standard no. 6 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-243-4877

Externally Relieved Body Screw - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.