NSN 5305-00-244-2364

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-244-2364

View Online at https://aerobasegroup.com/nsn/5305-00-244-2364
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.850 inches and 0.910 inches
Fastener Length:
Between 1.730 inches and 1.790 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.543 inches and 0.562 inches
Head Height:
Between 0.240 inches and 0.250 inches
Shoulder Diameter:
0.371 inches first shoulder and 0.373 inches first shoulder
Shoulder Length:
0.850 inches first shoulder and 0.910 inches first shoulder
Single Shear Strength:
3700 pounds per square inch
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
0.188 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
140000 pounds per square inch
Shoulder Shape:
Round first shoulder
Material:
Steel
Material Specification:
Mil-s-21472 military specification single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment response
Thread Series Designator:
Unf

NSN 5305-00-244-2364

Shoulder Screw - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-s-21472 spec.

Shelf Life: