NSN 5305-00-244-2882

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-244-2882

View Online at https://aerobasegroup.com/nsn/5305-00-244-2882
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.251 inches and 0.301 inches
Fastener Length:
Between 1.199 inches and 1.229 inches
Head Style:
Pan
Head Diameter:
Between 0.306 inches and 0.322 inches
Head Height:
Between 0.105 inches and 0.115 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Screw Material:
Steel comp 4140 or steel comp e4340 or steel comp 8740
Screw Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military
specification 3rd material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas623 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5305-00-244-2882

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.