

View Online at <https://aerobasegroup.com/nsn/5305-00-245-8823>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.381 inches and 0.448 inches

Fastener Length:

Between 0.703 inches and 0.750 inches

Head Style:

Flat countersunk undercut

Head Diameter:

Between 0.377 inches and 0.381 inches

Head Height:

Between 0.044 inches and 0.046 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.190 inches

Grip Length:

Between 0.302 inches and 0.322 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Countersink Angle:

100.0 degrees

Special Features:

Furnished with one rubber o-ring

Material:

Steel comp 8735 or steel comp 4130 or steel comp 4140 or steel comp 4340 or steel comp 8740

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0